



Style of product may vary from picture

## PRODUCT DIMENSIONS

	INCHES	CENTIMETERS
A	48 1/16	122.1
B <sup>1</sup>	****NaN****	
C	23.796	60.4
D <sup>2</sup>	25 1/4	64.1
E <sup>3</sup>	52 9/16	133.5
F <sup>4</sup>	****NaN****	
G <sup>5</sup>	83 1/16	211.0
H <sup>6</sup>	83 1/16	211.0
J <sup>7</sup>	83 3/8	211.8
K <sup>9</sup>	N/A	N/A
L	83 3/4	212.7
M	47 1/2	120.7
N	24	61.0

## MODEL SKUs

JS48CSDBDA

## NOTES:

1. Depth with doors closed, including handle.
2. Depth with doors closed, excluding handle.
3. Depth with doors open at 90 degrees.
4. Width with doors open at 90 degrees, including handles.
5. Height to top of refrigerator.
6. Height to top of refrigerator including door hinge.
7. Height to top of refrigerator door trim (if needed for trim models).
8. When installing refrigerator in or near a corner, allow enough room for door to open without interfering with cabinet drawers or hardware.
9. Width closed including door and trim.
10. Add 1"/2.5 cm to depth (B) for extended handle kit, if used on framed model.
11. Add 2"/5.08 cm to width (F) for extended handle kit, if used on framed model.

**Electrical requirements:** Adequately wired individual 120V A/C, 60Hz approved electrical circuit.  
Use required fuse (15 amp) or comparable circuit breaker.