# **MAT15MN**

**ENERGY ADVANTAGE™** 

MAYTAG® COMMERCIAL TOP-LOAD WASHER





#### **LEGENDARY MAYTAG DEPENDABILITY**

Maximizing your equipment investment for over half a century.



### **FOR YOUR OPERATION:**

- The Most Efficient, Best Cleaning Top-Load Washer From Maytag
- Extra-Large Lid And Tub Opening
- Dial-A-Fabric™ Cycle Selection
- Cycle Stage Indicator Lights
- Front Access For Easier Self-Service
- Extra Large Tub Capacity

### **BUILT-TO-LAST™ FEATURES:**

- Premium Porcelain-Enamel Top
- · Beltless Design
- Dependable Direct Drive Transmission
- Self Cleaning Pump
- Reliable Electro-Mechanical Controls
- Best Warranty In The Business



LAUNDRY SOLUTIONS
YOU CAN DEPEND ON.



www.maytagcommerciallaundry.com

## OUR COMMITMENT TO DEPENDABLE QUALITY

At Maytag, we believe durable goods should remain just that. That's why every Maytag® product is constructed of the highest-quality materials and with the utmost in precision craftsmanship. It's also why we stand behind our equipment with solid service and support from our professional Maytag laundry suppliers. Simply put, when you choose Maytag® products, you ensure your peace of mind.




### Maytag<sup>®</sup> Energy Advantage<sup>™</sup> Top-Load Washer

### **MECHANICAL NON-COIN**

WASHER SPECIFICATIONS MODEL	MAT15MN
MOTOR	NINICI I AIVI
Single-phase, reversible, thermoprotected, high torque	· // 07\
HP (kw)	1/2 (.37)
APPROXIMATE WATER USAGE — gallons (liters)	4.4.45.5\*
Average hot water usage per cycle	4.1 (15.5)*
Average total water usage per cycle	30 (113.5)*
ELECTRICAL RATING	
Domestic model — voltage	120V/60 Hz
Export model — voltage	220-240V/50Hz
BREAKER/FUSE REQUIREMENT	
Domestic model — amps	15
Export model — amps	10
CYLINDER	
Volume — cu. ft. (liters)	3.2 (90.6)
Diameter — in. (mm)	20.3 (526)
Depth — in. (mm)	17.4 (442)
LID OPENING	
In. (mm)	18 (457)
EXTRACT SPEED	
Maximum rpm	640
Maximum g-force	120
OPERATING PRESSURE	
Psi (bar)	20-100 (1-8)
INLET HOSE LENGTH	
Ft. (m)	4.5 (1.37)
DRAIN HOSE LENGTH	
Ft. (m)	4.4 (1.34)
APPROXIMATE WEIGHT	
Crated — lbs. (kg)	179 (81.2)
Uncrated — lbs. (kg)	165 (74.8)

Average based on J1 testing with factory preset cycles.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.





NEW YORK CITY









### **5 YEARS ON ALL PARTS**

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage.

See complete warranty for details.