



Job Specifications

INSTANT HOT WATER DISPENSERS

Model GN Instant Hot Water Dispenser



Submittal Sheet

The compact gooseneck design dispenses instant near-boiling 200°F water.

- Hot Only Dispenses near-boiling 200°F water
- 35% more near-boiling water from larger ²/₃ gallon stainless steel tank
- · Easy to adjust temperature control
- Tool-free tank connections and dry start protection to ease installation
- Provides 60 cups/hour of near-boiling water
- 3-Year We Come To You™ In-Home Service Warranty*
- 120 volts, 750 watts, 6.25 amps
- Available in white, biscuit, and black or chrome with a black base and handle
- * The complete In-Sink-Erator warranty is included in the Installation, Care & Use Booklet packed with each unit.

Sample Specification

- Capacity: ²/₃ gallon tank dispenses 60 cups of 200°F water per hour
- Electrical: 120 volts A.C., 750 watts, 6.25 amp heating element with grounded three (3) prong plug
- Thermostat: Snap action, adjustable from 160°F to 210°F (factory pre-set at approximately 200°F)
- Insulation: Meets U.L. 94HF-1 flammability specification
- Valve: Instant, self-closing
- Recommended Supply Pressure: 30-125 psi
- Shipping Weight: Approximately 9.75 lbs.

To ensure optimum performance, maximum distance between tank and dispenser head should be 16" or less

Specifications

Capacity	² / ₃ gallon tank dispenses 60 cups of 200°F water per hour
Electrical	120 volts A.C., 750 watts, 6.25 amp heating element with grounded three (3) prong plug
Thermostat	Snap-action, adjustable from 160°F to 210°F (factory pre-set at 200°F)
Insulation	Meets U.L. 94HF-1 flammability specification
Valve	Instant, self-closing
Recommended Supply Pressure	30-125 psi
Shipping Weight	Approximately 9.75 lbs.
Required Hole Diameter	1 ¼" - 1 ½"





The Emerson logo is a trademark and a service mark of Emerson Electric Co. In-Sink-Erator is a division of Emerson Electric Co.