DCM24 ACTK27, ACTK30, ACTK36, AOCTK27, AOCTK30




Revised 08/05/08

Convection Microwave Oven


1/1

PLANNING GUIDE



MICROWAVE AND TRIM KIT

*Bare minimum spacing: Includes additional space to avoid scrapping/vibration.



DCM24 SPECIFICATIONS

Shipping Weight: 60 lbs. Circuit Required: 120 Vac,

1 1/4"


(32mm)


15 Amp. dedicated

Total (Connected Load): 1.6 Kw (13 Amp.)

NOTE:

- 1. 24" (610mm) minimum exterior cabinet depth.
- 2. See the Combination Installation (CI) section if installing with a wall oven, or warming oven.
- 3. 3/4" (19mm) support platform (flush with cutout).
- 4. Microwave is supplied with a 42" (1067mm) power cord, with a three prong grounded plug.





(Epicure® or Millennia™ Trim Kit - use these models when stacking with the Classic/Renaissance Wall Oven)

"A"

20 1/8"
(511mm)

ACTK OVERALL DIMENSIONS

AOCTK OVERALL DIMENSIONS

(Epicure® or Millennia™ Trim Kit - use these models when stacking with the Discovery Wall Oven)

Model No.		"A" Overall Width	"B" Cutout Width	"D" Cutout Height	Top Overlay	Bottom Overlay	Approximate Shipping Weight
ACTK27	For Use With Wall Oven Models: EOR, MOR, EC, MC, PC	27" (686mm)	25 1/4" (641mm)	19 1/8" (486mm)	1/2" (13mm)	1/2" (13mm)	15 lbs,
ACTK30		30" (762mm)	28 1/4" (718mm)	19 1/8" (486mm)			16 lbs.
ACTK36		36" (914mm)	25" (635mm)	19 1/8" (486mm)			20 lbs.
AOCTK27	For Use With Wall Oven Models: EO, MO, PO	27" (686mm)	25 1/4" (641mm)	18 1/2" (470mm)	5/8" (16mm)	1" (25mm)	19 lbs.
AOCTK30		30" (672mm)	25 1/4" (641mm)	18 1/2" (470mm)			20 lbs.

Web: http://www.Dacor.com Corporate Phone: 800-793-0093