

**PWC362418**

**FEATURES**

- Heavy-duty stainless steel construction
- Handfinished with hemmed edges and welded seams
- Blower required (internal, in-line or remote blowers available)
- Recessed controls for sleeker look
- Infinite speed blower control
- Bright halogen lighting
- Heat sentry for safety
- Transition with backdraft minimizes backward flow of cold air
- Install with accessory duct cover for chimney-style hood
- Rigorously tested in our U.S. manufacturing facilities for decades of use
- Exceptional 24/7 support from our Customer Care team in Madison

**ACCESSORIES**

- Backsplash
- Backsplash with Warming Racks
- Make-Up Air Damper
- 38" high stainless steel backsplash with or without warming racks
- Make-up air damper
- Inline Blowers
- Internal Blowers
- Remote Blowers
- Pro Chimney Hood Duct Covers

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).



**BLOWER OPTIONS**

- 300 CFM Internal
- 450 CFM Internal
- 600 CFM Internal
- 900 CFM Internal
- 1200 CFM Internal
- 600 CFM Inline
- 1100 CFM Inline
- 600 CFM Remote
- 900 CFM Remote
- 1200 CFM Remote
- 1500 CFM Remote

**PRODUCT SPECIFICATIONS**

Model	PWC362418
Dimensions	36"W x 18"H x 24"D
Weight	78 lbs
Electrical Supply	110/120 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Discharge Location	Vertical
Discharge Dimensions	10" Round
Bottom of Hood to Countertop	30" to 36"

**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

**DIMENSIONS**

