

## DISPLAY

### AVAILABLE COLORS



Silver



Black



*DS-3211MT LANDSCAPE SHOWN IN BLACK  
(POLE STAND NOT INCLUDED)*

## KEY FEATURES

- 32" Pro Series True Outdoor All-Weather Digital Signage for permanent outdoor installation
- Bright 32"(1000 NIT) full HD, 1080p LED-LCD screen for improved outdoor viewing
- Interactive LG Innotek 10 point PCAP multi touch screen with anti-glare surface.
- Integrated Sharp touch controller. Plug and Play HID with Windows 7, 8 & 10, no calibration needed.
- Media Compartment for digital media player or fan less PC. (Opening: 7" x 12.5" x 3" deep / Interior: 8" x 14" x 2.5" deep)
- Direct Sunlight-Readable
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic backout
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air.
- Powder-coated rust-proof aluminum exterior for strength and durability.
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (5 degrees F). \*
- Ambient Light Sensor provides automatic dimming of backlight for night time viewing.
- Front tempered anti-reflective glass window provides added protection to LED-LCD screen, and safeguards against vandalism & abuse.
- RS232 serial control with discrete on, off, and input control.
- Rear IR receiver (located in the cable-entry compartment).
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Water-tight media player/cable compartment accommodates a variety of media players including Brightsign<sup>®</sup>
- Weatherproof detachable 20W speaker module (not included), remote control, and control buttons.
- Side control button lock-out prevents unauthorized users from changing the programming.
- Includes warranty and manual

# SunBriteDS<sup>®</sup>

## Outdoor Digital Signage

<b>SCREEN</b>	<p><b>SCREEN</b> 32" Diagonal Color Active Matrix TFT LED-LCD</p> <p><b>RESOLUTION</b> 1920 x 1080 Full-HD 1080p</p> <p><b>ASPECT RATIO</b> 16:9</p> <p><b>CONTRAST RATIO (32", 47" &amp; 55")</b> 1300:1</p>	<p><b>FRAME RATE</b> 60hz</p> <p><b>VIEWING ANGLE</b> 178° x 178°</p> <p><b>RESPONSE TIME</b> 25ms</p> <p><b>TV FORMATS (32", 47" &amp; 55")</b> 1080p, 1080i, 720p, 720i, 480p, 480i</p>
<b>CONNECTIONS</b>	<p><b>RF</b> Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p><b>HDMI</b> HDMI™ Input x2</p> <p><b>VIDEO COMPOSITE</b> S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p><b>VIDEO COMPONENT</b> YPbPr plus Stereo Audio x2</p> <p><b>PC</b> 15-pin D-sub VGA plus Stereo Audio</p> <p><b>CONTROL SET</b> RS232 Serial, Discrete IR Control, Concealed IR Window</p>	<p><b>TOUCH INTERFACE</b> USB 2.0 type B female jack. USB type A to B cable required (not included)</p> <p><b>AUDIO OUT</b> Digital SPDIF Audio(fixed) Analog 1/8" headphone jack (variable)</p> <p><b>SPEAKERS</b> 20 WATT detachable speaker module (not included)</p> <p><b>INPUT POWER</b> 100-240 VAC, 50-60 Hz,</p>
<b>TEMPERATURE TOLERANCES</b>	<p><b>OPERATING TEMP</b> 5° to 122° F. (-15° to 50°C.)*</p> <p><b>NON-OP. TEMP</b> -24° to 122° F. (-31° to 50°C.)*</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied.</p>	
<b>PHYSICAL SPECS</b>	<p><b>ACCESSORIES INCLUDED</b> Weatherproof remote control</p> <p><b>EXTERIOR</b> Powder-coated aluminum.</p> <p><b>EXTERIOR COLORS</b> Black, Silver</p> <p><b>TV DIMENSIONS</b> (3211MTSL) 31.08"(789mm) W x 18.87"(479mm) H x 5.49"(139mm) D (3211MTSP) 18.87"(479mm) W x 31.08"(789mm) H x 5.49"(139mm) D</p> <p><b>RESIDENTIAL WARRANTY</b> Two-year parts and labor.</p> <p><b>COMMERCIAL WARRANTY</b> Two-year parts and labor.</p>	