



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Refrigerator



eco friendly
R600a Refrigerant



JOB	
AREA	
ITEM NO.	
MODEL NO.	



Glass Door Model



Solid Door Model

MODELS	DESCRIPTION
HH24RS-4-1R/L	Indoor Shallow Depth Refrigerator Solid Stainless Steel Door
HH24RS-4-2R/L	Indoor Shallow Depth Refrigerator Solid Panel Ready Door
HH24RS-4-3R/L	Indoor Shallow Depth Refrigerator Stainless Steel Glass Door
HH24RS-4-4R/L	Indoor Shallow Depth Refrigerator Panel Ready Glass Door
HH24RO-4-1R/L	Outdoor Shallow Depth Refrigerator Solid Stainless Steel Door
HH24RO-4-2R/L	Outdoor Shallow Depth Refrigerator Solid Panel Ready Door
HH24RO-4-3R/L	Outdoor Shallow Depth Refrigerator Stainless Steel Glass Door
HH24RO-4-4R/L	Outdoor Shallow Depth Refrigerator Panel Ready Glass Door

KEY PRODUCT FEATURES AND BENEFITS

- Industry exclusive 18" shallow depth for ultimate design flexibility in tight spaces
- Industry's largest selection of ADA compliant models for accessible and aging in place designs
- 1000 BTU/hr capacity delivers industry's most energy efficient cool down; indoors or outdoors
- Up to 70% faster cooling speeds than leading competitor
- Variable speed compressor minimizes sound; up to 30% quieter than competitors

Quick Features:

- Perlick Anti-Condensation System™ eliminates condensation from forming on the cabinet (outdoor models only)
- Full extension shelving provides faster and safer product access with no reaching in the back of the cabinet; shelves fully extend on vibration dampened stainless steel ball bearing glides
- Industry's best full 6 year warranty for owner ease of mind
- Commercial-grade all stainless steel interior and exterior provide superior durability and easy cleaning
- Available with stainless steel or panel ready door to match your design style
- Audible door alarm warns user if door is held open
- Selectable blue or white LED lighting
- R600a Natural Refrigerant offers maximum energy efficiency with zero ozone depletion potential
- Storage for up to 68 cans



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Refrigerator

MODEL NUMBERS		HH24RS	HH24RO
MODEL DESCRIPTION		18" Indoor Refrigerator	18" Outdoor Refrigerator
ATTRIBUTES			
Perlick Anti-Condensation System		NO	YES
Energy Star Certified		YES	YES
OVERALL DIMENSIONS	Width - in. (mm)	23-7/8" (606 mm.)	23-7/8" (606 mm.)
	Depth - in. (mm)	18" (457 mm.)	18" (457 mm.)
	Height - in. (mm)	32" (813 mm.)	32" (813 mm.)
OPENING DIMENSIONS	Width - in. (mm)	24" (610 mm.)	24" (610 mm.)
	Depth - in. (mm)	18" (457 mm.)	18" (457 mm.)
	Height - in. (mm)	32-1/4" (819 mm.)	32-1/4" (819 mm.)
INTERNAL VOLUME Net. Cu. Ft.		3.1 cu. ft.	3.1 cu. ft.
SHIPPING WEIGHT Lbs. (kg.)		185 lbs (83.91 kg.)	185 lbs (83.91 kg.)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115 VAC/60 Hz/1 Ph	115 VAC/60 Hz/1 Ph
	Running Load Amps	2.2 amps	2.2 amps
	Electrical Connection	Cord connected	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P	NEMA 3 Prong 5-15P
	Cord Length	6'	6'
	Defrost Initiation	Automatic	Automatic
	Defrost Type	Off cycle	Off cycle
	Thermostat	Digital	Digital
	Lighting Type	LED	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (50g)	R600a (50g)
	Expansion Device	Capillary Tube	Capillary Tube
	Temperature Settings F°(C°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)	33° (0.5°) - 48° (8.8°) Factory Set Point 36° (2.2°)
	Heat Rejection (at 75°F)	350 BTU/hr	350 BTU/hr
	Pull Down Capacity	1000 BTU/hr	1000 BTU/hr
	Front Vented	Yes	Yes
PLUMBING		None Required	None Required

ACCESSORIES

MODEL NOS.	DESCRIPTION
(L)	Factory Installed Lock
67992-L/R	Stacking Kit for HH24 models
67360	6" Toe Kick and Riser

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com.




SIGNATURE SERIES SHALLOW DEPTH
18" Depth Refrigerator

CUSTOMER MODEL NUMBER	REGULATORY MODEL NUMBER	Hinge Side	Lock
HH24RS-4-1L	HH24RS4C-00-SLF0R	Left	No
HH24RS-4-1R	HH24RS4C-00-SRF0R	Right	No
HH24RS-4-2L	HH24RS4C-00-PL00R	Left	No
HH24RS-4-2R	HH24RS4C-00-PR00R	Right	No
HH24RS-4-3L	HH24RS4C-00-TLF0R	Left	No
HH24RS-4-3R	HH24RS4C-00-TRF0R	Right	No
HH24RS-4-4L	HH24RS4C-00-RL00R	Left	No
HH24RS-4-4R	HH24RS4C-00-RR00R	Right	No
HH24RS-4-1LL	HH24RS4C-00-SLF1R	Left	Yes
HH24RS-4-1RL	HH24RS4C-00-SRF1R	Right	Yes
HH24RS-4-2LL	HH24RS4C-00-PL01R	Left	Yes
HH24RS-4-2RL	HH24RS4C-00-PR01R	Right	Yes
HH24RS-4-3LL	HH24RS4C-00-TLF1R	Left	Yes
HH24RS-4-3RL	HH24RS4C-00-TRF1R	Right	Yes
HH24RS-4-4LL	HH24RS4C-00-RL01R	Left	Yes
HH24RS-4-4RL	HH24RS4C-00-RR01R	Right	Yes
HH24RO-4-1L	HH24RO4C-00-SLF0R	Left	No
HH24RO-4-1R	HH24RO4C-00-SRF0R	Right	No
HH24RO-4-2L	HH24RO4C-00-PL00R	Left	No
HH24RO-4-2R	HH24RO4C-00-PR00R	Right	No
HH24RO-4-3L	HH24RO4C-00-TLF0R	Left	No
HH24RO-4-3R	HH24RO4C-00-TRF0R	Right	No
HH24RO-4-4L	HH24RO4C-00-RL00R	Left	No
HH24RO-4-4R	HH24RO4C-00-RR00R	Right	No
HH24RO-4-1LL	HH24RO4C-00-SLF1R	Left	Yes
HH24RO-4-1RL	HH24RO4C-00-SRF1R	Right	Yes
HH24RO-4-2LL	HH24RO4C-00-PL01R	Left	Yes
HH24RO-4-2RL	HH24RO4C-00-PR01R	Right	Yes
HH24RO-4-3LL	HH24RO4C-00-TLF1R	Left	Yes
HH24RO-4-3RL	HH24RO4C-00-TRF1R	Right	Yes
HH24RO-4-4LL	HH24RO4C-00-RL01R	Left	Yes
HH24RO-4-4RL	HH24RO4C-00-RR01R	Right	Yes



SIGNATURE SERIES SHALLOW DEPTH
18" Depth Refrigerator



* - Leg levelers can add 3/4" to these dimensions when fully extended.

